



APPLICATIONS AND PROPERTIES

Mandrel built hose for driving cement powder, concrete and granulates at low pressure.

COMPOSITION

- Interior tube:** NR natural rubber resistant to abrasion.
- Reinforcement:** High tenacity synthetic braided.
Intermediate rubber layer ensures perfect adherence between inner tube and cover.
It incorporates copper wire for electrostatic discharge.
- External cover:** Smooth black NR/EPDM rubber resistant to abrasion, weathering and severe operating conditions.
Surface with wrapped finish.

Code	Ø ID		Ø OD	Thick-ness	Weight	Work Pressure		Bend Radius	Roll Length
	inch	mm				mm	mm		
0150070082	2 3/4	70	82	6,00	2,010	6	90	300	40
0150076088	3	76	88	6,00	2,330	6	90	350	40
0150080092	3 1/8	80	92	6,00	2,470	6	90	400	40
0150090101	3 1/2	89	101	6,00	2,550	6	90	450	40
0150102114	4	102	114	6,00	3,550	6	90	500	40

- Note:** It can be supplied cut to size.
- Safety factor:** 3:1
- Temperature:** -20°C to +70°C
- Marking:** T-17 TUBIGOMMA CEMENT DISCHARGE 6 BAR (90 PSI)
- Marking type:** Letters / strip in green.
- Norm:** ISO 1307