



## APPLICATIONS AND PROPERTIES

It is extremely flexible, easy to handle and fold. Low pressure applications or gravity exchanges of loading and unloading of tanks. It is specially designed to handle hydrocarbons and chemicals.

## COMPOSITION

<b>Inner lining:</b>	Polypropylene sheets.
<b>Inner helix:</b>	Polypropylene coated galvanized steel.
<b>Outer helix:</b>	Galvanized steel.
<b>Cover:</b>	Polypropylene.
<b>Colour:</b>	Green.

Code	Ø ID inch	Weight kg/m	Work Pressure		Bend Radius mm	Roll Length m/roll
			bar	PSI		
0191025	1	0,750	10	150	68	30
0191032	1 1/4	0,970	10	150	74	30
0191040	1 1/2	1,300	10	150	105	30
0191050	2	2,010	10	150	190	30
0191065	2 1/2	2,900	10	150	225	30
0191080	3	3,400	10	150	290	30
0191100	4	5,950	10	150	320	30

<b>Note:</b>	This material is always supplied cut to size and with couplings.
<b>Safety factor:</b>	5:1
<b>Temperature:</b>	-20°C to +100°C
<b>Marking:</b>	CHEMICOMP PZ 10 BAR SOMAFLEX EN13765-BS5842