



APPLICATIONS AND PROPERTIES

Hose of flat structure, flexible, light and resistant to the atmospheric agents and to great part of chemical products, fertilizers and acids.

Used in agriculture for irrigation, construction, shipbuilding and public works.

COMPOSITION

Tube: Flexible blue PVC.
Reinforcement: High tenacity synthetic thread.

Code	Ø ID		Ø OD mm	Thick- ness mm	Weight kg/m	Work Pressure		Roll Length m/roll
	inch	mm				bar	PSI	
0203025	1	25	29	2,00	0,200	9	135	50-100
0203030	1 3/16	30	34	2,00	0,220	8	120	100
0203032	1 1/4	32	36	2,00	0,230	8	120	100
0203035	1 3/8	35	39	2,00	0,250	8	120	100
0203038	1 1/2	38	42	2,00	0,270	8	120	100
0203040	1 9/16	40	44	2,00	0,290	8	120	50-100
0203045	1 3/4	45	49	2,00	0,320	7	105	50-100
0203051	2	51	56	2,50	0,360	7	105	50-100
0203060	2 3/8	60	65	2,50	0,480	7	105	50
0203065	2 1/2	65	70	2,50	0,500	7	105	50
0203070	2 3/4	70	75	2,50	0,570	7	105	50
0203077	3	77	82	2,50	0,600	6	90	50

Code	Ø ID		Ø OD mm	Thick- ness mm	Weight kg/m	Work Pressure		Roll Length m/roll
	inch	mm				bar	PSI	
0203080	3 1/8	80	85	2,50	0,660	6	90	50
0203090	3 1/2	90	95	2,50	0,760	6	90	50
0203103	4	103	108	2,50	0,880	6	90	50
0203110	4 3/8	110	115	2,50	1,000	6	90	50
0203127	5	127	133	3,00	1,250	6	90	50
0203153	6	153	159	3,00	1,580	6	90	50
0203203	8	203	209	3,00	2,200	4	60	50

Note: It can be supplied cut to size.
Safety factor: 3:1
Temperature: -10°C to +60°C
Marking: ACUAFLAT SUPER Ø MM