



APPLICATIONS AND PROPERTIES

Flexible PVC hose for plumbing installations.

It is intended for drains of sanitary equipment, air conditioning or pumping in swimming pools. It has high resistance to sewage, detergents and chemicals.

COMPOSITION

Tube: Smooth flexible PVC. Grey or white.

Reinforcement: Rigid PVC helix inside the hose.

Code	Ø ID		Ø OD	Thick-ness	Weight	Work Pressure		Vacuum	Bend Radius	Roll Length
	inch	mm				mm	mm			
0251012	1/2	12	16	2,00	0,100	7	105	7	39	25/50
0251016	5/8	16	20	2,00	0,155	7	105	7	48	25/50
0251020	3/4	20	25	2,50	0,240	7	105	7	60	25/50
0251026	1	26	32	3,00	0,370	5	75	7	78	25/50
0251027		27	32	2,50	0,334	5	75	7	81	25/50
0251034		34	40	3,00	0,480	5	75	7	102	25/50
0251035		35	40	2,50	0,400	5	75	7	105	25/50
0251043		43	50	3,50	0,685	5	75	7	129	25/50
0251055		55	63	4,00	1,000	5	75	7	165	25/50

Note: It can be supplied cut to size.

Temperature: -30°C to +60°C

Marking: HIDROTRANS Ø MM

Norm: UNE EN ISO 3994