



APPLICATIONS AND PROPERTIES

Suction and conduction of light particles (dust, fibers, ...)
 Vacuum cleaners, industrial and domestic, systems for drying and extraction of welding fumes.
 Extremely flexible, resistant to ozone and ultraviolet rays.

COMPOSITION

Tube: Double layer of PVC.

Reinforcement: Reinforcement with radial and axial fabric. PVC coated steel spiral.

Code	Ø ID		Ø OD	Thick-ness	Weight	Work Pressure	Vacuum	Bend Radius	Roll Length
	inch	mm							
0254025	1	25	31	3,00	0,170	0,56	2,0	25	15
0254032	1 1/4	32	38	3,00	0,260	0,50	2,0	32	15
0254038	1 1/2	38	44	3,00	0,350	0,46	2,0	38	15
0254041	1 3/16	41	47	3,00	0,370	0,46	1,8	41	15
0254044	1 3/4	44	50	3,00	0,410	0,43	1,6	44	15
0254051	2	51	57	3,00	0,440	0,43	1,5	51	15
0254063	2 1/2	63	69	3,00	0,490	0,33	1,4	63	15
0254076	3	76	82	3,00	0,550	0,26	1,0	76	15
0254089	3 1/2	89	95	3,00	0,600	0,23	0,9	89	15
0254102	4	102	108	3,00	0,640	0,20	0,8	102	15

Note: It can be supplied cut to size.

Temperature: 0°C to +80°C