

APPLICATIONS AND PROPERTIES

The Barcelona fitting is the most widely used for fire-fighting systems.

Follow the UNE 23400 standard.

Sexless fittings with 3 pins that secure the closure by facing each other.

They can withstand working pressures up to 15 bar.

The threads are of type BSPP (thread parallel gas).

The material used in fittings is aluminum (stamped or forged) or brass.

The gaskets are from NBR.

MODELS



ND - ØHOSE	HOSE		
	STAMP. ALUM.	FUSED ALUM.	BRONZE
25 - 19 mm	060601012	-	-
25 - 25 mm	060601010	-	060601210
45 - 38 mm	-	060601118	060601218
45 - 45 mm	060601020	060601120	060601220
45 - 51 mm	-	060601122	060601222
70 - 63 mm	-	060601128	060601228
70 - 70 mm	060601030	060601130	060601230
100 - 100 mm	060601040	-	-



FEMALE THREAD

ND - F. THREAD	STAMP. ALUM.	FUSED ALUM.	BRONZE
25 - 3/4"	060602005	-	-
25 - 1"	060602010	060602110	060602210
45 - 1 1/2"	060602020	060602120	060602220
70 - 2"	-	-	-
70 - 2 1/2"	060602030	060602130	060602230
100 - 2 1/2"	060602033	-	-
100 - 3 1/2"	060602037	-	-
100 - 4"	060602040	-	-



MALE THREAD

ND	STAMP. ALUM.	FUSED ALUM.	BRONZE
25 - 3/4"	060603005	-	-
25 - 1"	060603010	060603110	060603210
45 - 1 1/2"	060603020	060603120	060603220
70 - 2 1/2"	060603030	060603130	060603230
100 - 3 1/2"	060603037	-	-
100 - 4"	060603040	-	-



PLUG

ND	STAMP. ALUM.	FUSED ALUM.	BRONZE
25 mm	060604010	-	060604210
45 mm	060604020	060604120	060604220
70 mm	060604030	060604130	060604230
100 mm	060604040	-	-



REDUCTION

ND TO ND	STAMP. ALUM.	FUSED ALUM.	BRONZE
45 a 25 mm	060605010	-	060605210
70 a 45 mm	060605020	060605120	060605220
100 a 70 mm	060605030	-	-

GASKETS



GASKETS

ND	FITTING	FLAT GASKET
25 mm	060606010	060607010
45 mm	060606020	060607020
70 mm	060606030	060607030
100 mm	060606040	-